

**DECLARATION OF PERFORMANCE**  
**N° 0007-106**

1. Unique identification code of the product-type:  
*Suspended ceiling: substructure components*
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):  
*Wall angle (see label)*
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:  
*Suspended ceiling substructure components*
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):  
*SAINT-GOBAIN EUROCOUSTIC*  
*1 place Victor Hugo, 92411 Courbevoie, France*  
[www.eurocoustic.com](http://www.eurocoustic.com)
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):  
*Not applicable*
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
*AVCP System 3 or 4 for reaction to fire*  
*AVCP System 3 for load bearing capacity*  
*AVCP System 4 for durability*
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:  
*For the products Alu, COR and EuroColor (in the table below), the CSTB (n° 0679) or the MPA (n° 0761) performed a determination of the product-type on the basis of type testing (based on sampling carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product under system 3 for the characteristic reaction to fire.*  
*It issued tests reports.*

*Products with PVC surfacing are classified F according to Commission Decision 2000/147/CE (AVCP System 4).*

*For products different from those aforementioned, it's not required to be tested for reaction to fire; they are classified A1 according to Commission Decisions 96/603/CE for products made up in galvanized steel or 2010/737/UE for products in steel covered by polyester (AVCP System 4).*

*The TNO (n° 1153) performed a determination of the product-type on the basis of type testing (based on sampling carried out by the manufacturer), type calculation, tabulated*

values or descriptive documentation of the product under system 3 for the characteristic load bearing capacity.

It issued tests reports.

A determination of the product-type on the basis of type testing, type calculation, tabulated values or descriptive documentation of the product under system 4 for the characteristic durability was performed.

No tasks for the notified body.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

9. Declared performance

Essential characteristics				
Product description	Reaction to fire	Load bearing capacity		Durability: Corrosion protection
		Fixture spacing mm	Admissible point load (Feff 0.8) N	
19x19 wall angle	A1	NPD	NPD	Class B
24x19 wall angle	A1	250	39	Class B
24x19 <b>Corro Plus</b> wall angle	A1	250	39	Class C/D*
24x19 wall angle - <b>EuroColor or other colors</b>	A2-s1, d0	250	39	Class B
24x24 wall angle	A1	NPD	NPD	Class B
24x35 wall angle	A1	NPD	NPD	Class B
30x30 wall angle	A1	NPD	NPD	Class B
30x30 wall angle <b>EuroColor or other colors</b>	A2-s1, d0	NPD	NPD	Class B
40x40 wall angle	A1	NPD	NPD	Class B
Bendable wall angle ( <b>PVC-coated</b> )	E	NPD	NPD	Class B
Hollow joint wall angle	A1	NPD	NPD	Class B
Clamping edge	A1	NPD	NPD	Class B
Wall clamping edge	A1	NPD	NPD	Class B
Wall clamping edge - <b>EuroColor or other colors</b>	A2-s1, d0	NPD	NPD	Class B
F profile	A1	NPD	NPD	Class B

\* Suitable for specific Class D situations, based on an expert opinion (Table 8 in EN 13964: 2014)  
All the essential characteristics listed in the first line in this table are corresponding to those described in NF EN 13964:2014.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Mr Eric Escalettes  
Director B.U. Eurocoustic Ceiling  
Courbevoie, August 29th 2018

